

# Marine Gasoil 0,005% S - Dyed

Marine Gasoil, Denmark

## Description

Marine Gasoil is a low viscosity gasoil with boiling point range from 200°C. to 385°C. The Marine Gasoil is classified fire danger class III-1 in Denmark (Flash Point higher than 55°C. and lower than 100°C. and the product is not soluble in water).

## Application

Marine Gasoil is used as fuel in the marine marked. Marine Gasoil 0,005%S (50 ppm S) - Dyed contains dye substance according to Danish Tax Ministry legislation no. 983 of October 18<sup>th</sup>, 2005 regarding dying of gasoil and kerosene in Denmark and must only be used for applications described in the legislation.

Note: According to legislation by the Ministry of environment then Marine Gasoil 0,005% S - Dyed is not allowed for use in vehicles.

## Specification

Marine Gasoil 0,005% S - Dyed meets the requirements for DMA in ISO 8217:2017.

## Typical data

Marine Gasoil - 0,005% S	Method	Data
Density, 15 °C., g/l	EN12185	820-870
Viscosity, 40°C., cSt. Min. - Max.	ASTM D 445	2,0-3,7
Flash Point, min. °C.	EN ISO 2719	61
Sulphur, max. weight %	ASTM D 5453	0,005
Water, max. mg/kg	EN12937	150
Water, max. mg/kg	ASTM D 1744	150
Conradsen Carbon Residue - @10% distillation residue, max. vægt%	EN 10370	0,15
Ash max. weight %	EN 6245	0,01
Destillation T 85%, max. °C.	EN 3405	360

## Cold Flow Properties

	Method	Data
Cold Filter Plugging Point (CFPP), max. °C.	EN116	÷20
Cloud Point, max. °C	EN23015	÷8



# Marine Gasoil 0,005% S - Dyed

## Typical Environmental Data

---

Marine Gasoil - 0,005% S	Data
SO <sub>2</sub> emission, g/l	0,08
TTW CO <sub>2</sub> emission, kg/l (Scope 1)	2,77

## Typical Energy Data

---

Marine Gasoil - 0,005% S	Data
Lower Heating value, typical MJ/kg	42,7
Energy content, kWh/l	10

## Definitions

---

Density:	Mass of substance per unit volume.
Viscosity:	Is a measure of the resistance to flow.
Flashpoint:	The lowest temperature at which the fuel deliver a vapor that is flammable.
Ash:	The weight of the ash left after the oil has combusted.
Cloud Point:	The temperature at which the fuel, when cooled, begins to congeal and present a cloudy appearance owing to the formation of wax.
CFPP:	The temperature at which the fuel can be expected to block a standard filter under standard conditions due to crystallization of paraffin.
Conradsen Carbon Residue:	Is indicating the tendency of carbon generation by heating the oil with deficit of oxygen.
Distillation, T 85%:	The temperature at which 85% of the product is vaporized.

## Material Safety Data Sheet

---

Guidance on Health and Safety is available on the Material Safety Data Sheet, which can be downloaded [www.dccenergi.dk](http://www.dccenergi.dk).

240924/POL  
MARINE GASOIL 0,005% DYED UK  
Product no.: DCC513058

